



---

## GENERAL DESCRIPTION

Stone Filter Fabric is a white, UV stabilized, needle-punched, non-woven polypropylene fabric.

## BASIC USE

Stone Filter Fabric is designed to be used in all Protected Membrane Roof (PMR) assemblies as a separator mat between the stone/gravel ballast and Dow STYROFOAM® insulation. Stone Filter Fabric serves three main functions. 1) It protects the underlying STYROFOAM insulation board from exposure to the sun. 2) It prevents the stone/gravel ballast from falling in between the joints in the insulation boards. 3) It prevents individual insulation boards from floating up out of the array.

## SIZES

Stone Filter Fabric is available in roll form with dimensions 13.5 feet in width and 360 feet in length (4,860 square feet per roll – approximately 4,500 “effective” coverage with 12 inch side and end laps). Each roll weighs approximately 101 pounds.

## TECHNICAL SPECIFICATIONS

PROPERTY	TEST METHOD	RESULT
COLOR		White
UNIT WEIGHT (oz/sq yd)	ASTM D3775	3.0
TENSILE GRAB STRENGTH (lb)	ASTM D4632	95
ELONGATION (%)	ASTM D4632	50
APPARENT OPENING SIZE (U.S. sieve)	ASTM D4751	50
FLOW RATE (gpm/ft2)	ASTM D4491	150