



---

## GENERAL DESCRIPTION

Flex-Flash F Vertical is an inorganic, woven, glass fiber fabric with an asphalt coating.

## BASIC USE

Flex-Flash F Vertical is designed to be used as the standard reinforcement material for Hydrotech's Monolithic Membrane 6125-FR (fabric reinforced) waterproofing assembly on vertical foundation walls. It is used to reinforce the membrane over the entire substrate. The 10 X 10 open weave allows the two coats of membrane to bond together easily through the fabric. Unadhered pockets between the layers of membrane, that can be common with the regular Flex-Flash F, are eliminated. The regular spunbonded polyester Flex-Flash F is still required for all horizontal and standard reinforcing applications, including inside corners (wall to footing) and outside corners (deck to wall).

Flex-Flash F Vertical is not intended to be used at drains, expansion joints or as an exposed flashing.

## SIZES

Flex-Flash F Vertical is available in standard widths of 6, 9, 12, 18, 24, 36 and 48 inches and a standard length of 150 feet.

## TECHNICAL SPECIFICATIONS

PROPERTY	TEST METHOD	RESULT
COLOR		Black
UNIT WEIGHT (oz/sq yd)	ASTM D1668	2.4
YARN COUNT (per inch)	ASTM D1668	10 X 10
BREAKING STRENGTH avg. (lb/in)	ASTM D1668	80 X 90