



GENERAL DESCRIPTION

Hydrodrain 700 is a composite drainage system of a three-dimensional drainage core and a woven filter fabric. The filter fabric is bonded to the top surface of the core dimples, preventing intrusion of the fabric into the flow channels during backfilling. The fabric extends 4" beyond the core and is bonded on one side of the core.

BASIC USE

The Hydrodrain drainage layer is ideal anywhere a subsurface drainage course is required. Typical applications include foundation walls, trench drains, planters, plaza decks and roof assemblies.

ADVANTAGES

- Reduces hydrostatic pressure on below-grade structures.
- Enhances conventional waterproofing systems by transmitting water into a collection system before it reaches the wall substrate.
- Prevents intrusions of soil, concrete, or grout into the flow channels.
- Materials are resistant to all known naturally occurring earth salts and minerals.

SIZES

The Hydrodrain drainage layer is available in roll form, 48 inches wide by 50 feet long. The geotextile overlaps the drainage core 4 inches on one side. Each roll covers 200 square feet and weighs 50 lb.

TECHNICAL SPECIFICATIONS

PROPERTY	TEST METHOD	GEOTEXTILE	DRAINAGE CORE
THICKNESS	ASTM D1777	--	0.40 in.
COMPRESSIVE STRENGTH	ASTM D1621	--	21,000 psf
FLOW "Q" @ 3600 psf; Hydraulic Gradient = 1	ASTM D4716	--	23 gal. / min. / ft. width
FLOW	ASTM D4491	18 gal. / min. / ft. width	--
PUNCTURE	ASTM D4833	120 lb.	--
GRAB TENSILE	ASTM D4632	370 X 250 lb.	--
APPARENT OPENING SIZE	CW-02215	70	--