



---

## GENERAL DESCRIPTION

A one-part, synthetic polymer based, aliphatic solvent lap seam sealant.

## BASIC USE

Specifically designed to caulk and seal the exposed sheet edges of Hydrotech's Flex-Flash UN (uncured neoprene) flashing membrane.

## ADVANTAGES

- Good adhesion to neoprene membranes as well as metal, wood and concrete
- Excellent resistance to ozone, ultra-violet and general weathering
- Excellent low temperature resistance

## TECHNICAL SPECIFICATIONS

Color:	Black	Weight/Gallon:	9.31 lb
Solvents:	Mineral Spirits	Solids Content:	66.4%
Base:	E.P.D.M. Rubber	Specific Gravity:	1.116
		Shelf Life:	9 months, unopened

## APPLICATION

- The flashing membrane sheet edge and immediate surrounding area should be clean and free of all contaminants (dirt, oil, water) as well as any excess Splicing Cement from the lap/seam.
- Apply a bead of Lap Sealant (approx. 3/8 inch) over the membrane sheet edge and "feather" the sealant so that it meets the membrane surfaces smoothly.
- The minimum recommended application temperature is 40 °F or higher.

## CAUTIONS

### FLAMMABLE LIQUID!

Do not use near open fire or flame and extinguish all smoking materials. Use only in well ventilated areas. Avoid prolonged breathing of vapors and contact with skin.

A Material Safety Data Sheet is available upon request.