



GENERAL DESCRIPTION

Perma-Board is a superior quality, semi-rigid, waterproof protection board composed of a rubberized asphalt core, reinforced with a non-woven fiberglass mat and sandwiched between two protective polypropylene layers.

BASIC USE

Perma-Board protection board is designed to be used as a protection board over Monolithic Membrane 6125, Liquid Membrane 6090 or Monolithic Membrane 7800, to protect the roofing/waterproofing membrane from damage due to backfilling, construction traffic, pavement/concrete overlays, etc. Perma-Board may be set directly into the MM 6125 or installed over a separation sheet and spot attached. Over LM 6090 and MM 7800, the waterproofing materials should be allowed time to cure/set before the Perma-Board is installed.

Perma-Board should be overlapped a minimum of 1 inch to insure complete protection of the roofing/waterproofing membrane.

ADVANTAGES

- Rubberized asphalt core provides excellent puncture resistance and durability.
- Dimensionally stable, will not shrink or curl.

SIZES

Perma-Board is available in sheets 39½ inches X 80 inches (1m X 2m) in 1/8 inch and 1/4 inch thickness'.

TECHNICAL SPECIFICATIONS

PROPERTY	RESULT
COLOR	Black
WEIGHT (lb./1/8" sheet)	15
WATER ABSORPTION (% , max.)	0.5
ASPHALT/RUBBER CONTENT (% approx.)	60/15
FIBERGLASS REINFORCEMENT (g./sq.m.)	95