



DESIGN

Standard Sizes

- From
- L18" W18" H18"
- Up to
- L48" W48" H48"

Material

- Aluminum - .125" thick Grade 5052-H32
- Corten Steel - .125" thick Grade A606/A588
- Mild Steel - .125" thick Grade A36

Base Styles

- Standard
- Inset
- Legs

Top Styles

- Straight sides
- Flange (standard)

Finishes

- Standard powder coating
- RAL powder coating
- Natural Rust - Steel only

FEATURES and OPTIONS

Leveling Feet with Swivel Head

- Standard 0-3" 200 lbs. cap.
- Heavy Duty 0-3" 5000 lbs. cap.

Lighting

- Integral wall wash/step lighting
- LED face light
- LED toe kick light

Drain Fittings

- Welded fitting to divert drain runoff and avoid staining on adjacent surfaces

Casters

- Non-marring swivel casters
- Locking swivel casters

Drip Tray

- Custom sized tray. Built to match coating and planter profile

Utility sleeve

- 1" ID sleeve to feed irrigation piping, electrical, speaker wire, etc.

Irrigation Reservoir

- Integral reservoir to enable planters to be self-irrigating

Plant Anchor Tie Off

- Integral tie off points to allow for attachment of stabilizing cables for root balls, or guy wires

** All joints formed or welded and ground smooth. Planters come standard with 1.25" drain holes. Custom sizing, shapes, and finishes available.*

TO SPECIFY

1. Select product, size, material
2. Select styles and finish
3. Select product-specific options

Refer to options section in catalog and specifications for standard and custom options. For questions, help specifying a product, or to place an order please contact an Architerra sales representative.

Shipping

Products are fabricated, finished, and shipped from Marysville, WA.



Marketed by Sika Corporation - Contact for further DETAILS and PRICING

100 Dan Road, Canton, MA 02021 • (800) 877-6125
 usa.sika.com/roofing • hydrotechusa.com

