

# Hydrotech® GardMat® LT

formerly known as GardMat® LT



BUILDING TRUST



## GENERAL DESCRIPTION

GardMat LT is a 100% coconut fiber matrix stitched together with biodegradable thread between biodegradable natural fiber top and bottom netting.

## BASIC USE

GardMat LT is designed to provide heavy duty wind and water surface erosion protection and assist with vegetation establishment for 18-24 months when installed over Hydrotech's LiteTop® growing media as part of Hydrotech's Garden Roof® Assembly. GardMat LT is typically used for plugs and/or potted plant vegetation plantings. Disk Anchors are used to fasten GardMat to LiteTop Growing Media surface.



## INSTALLATION

- Refer to Hydrotech's Garden Roof Installation Guidelines for specific installation instructions
- GardMat LT shall be installed as indicated in Hydrotech's Garden Roof Installation Guide
- Used with plugs and/or potted vegetation
- Can be used for slopes up to 1:1 (45°; 100%) maximum
- Good for up to 24 months where excellent vegetation coverage is needed before mat degradation

## TECHNICAL DATA

PROPERTY	TEST METHOD	RESULTS
WIDTH (feet)		8 feet wide
LENGTH (feet)		112.5 feet long
ROLL COVERAGE		100 sq. yards (900 SF) per roll
THICKNESS (inches)	ASTM D5199 / ECTC <sup>1</sup>	0.26
WEIGHT (oz/sqyd)	ASTM D5261	8.83
TENSILE STRENGTH (MD <sup>2</sup> - lb/ft)	ASTM D5035	342
TENSILE STRENGTH (TD <sup>3</sup> - lb/ft)	ASTM D5035	211
ELONGATION (MD - %)	ASTM D5035	7.6
ELONGATION (TD - %)	ASTM D5035	11.1
WATER ABSORPTION (%)	ASTM D1117 / ECTC	155
RESILIENCY (%)	ECTC	85
STIFFNESS / FLEXIBILITY (oz-in)	ASTM D1388 / ECTC	0.11
SMOLDER RESISTANCE ECTC		YES <sup>4</sup>

(values published are min. req)

1. (ECTC) Erosion Control Technology Council

2. MD = Machine Direction

3. TD = Transverse Direction

4. Material is smolder resistant according to ECTC Guidelines

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Poseyville, IN
Extraction/Harvesting Location		Poseyville, IN Atlanta, GA

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.