



NOTES:

1. FLEX-FLASH F MAY BE USED AT ALL CONCRETE-TO-CONCRETE AND CONCRETE-TO-CONCRETE BLOCK TRANSITIONS. FLEX-FLASH UN MUST BE USED AT ALL OTHER TRANSITIONS (i.e., CONC.-TO-GYP. BD., GYP. BD.-TO-GYP. BD., ETC.)
2. PENETRATION/CURB SURFACES MUST BE CLEAN AND FREE OF ALL RUST AND OTHER CONTAMINANTS.
3. FLASHING HEIGHTS AND CONTACT AREAS NOTED ARE MINIMUM REQUIREMENTS. GOOD ROOFING PRACTICE DICTATES THAT FLASHING TERMINATION POINTS EXTEND WELL ABOVE FINISHED BALLAST.

	Monolithic Membrane 6125-FR <small>ROOFING SYSTEMS</small>
	AMERICAN HYDROTECH, INC.

PRE-FLASHING WITH HYDROSEAL RESIN LIQUID FLASHING	
SCALE: NONE DATE: 12/01/17	R-10E

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.