

Hydrotech® Checker Block®

formerly known as Checker Block®




BUILDING TRUST



GENERAL DESCRIPTION

Checker Block is a castellated pervious concrete grid unit made of high strength concrete with steel reinforcement. Each unit is cast in a grid of truncated concrete pyramids joined by horizontal concrete connectors. The grid unit is a nominal 24" x 24" x 4" deep and fabricated in accordance with ASTM C1319. Each unit is manufactured by Reading Rock/Ackerstone/Nicolock/Hastings Pavement Company and marketed by American Hydrotech for exclusive use in the Garden Roof® Assembly.



BASIC USE

Checker Block is used to provide enhanced wind ballasting as a part of the Garden Roof Assembly. It can be planted with InstaGreen® Carpet, intensive material or sedum/perennial plugs.

INSTALLATION

- Refer to Hydrotech’s Checker Block Tech Data Sheet for specific installation instructions.
- Stainless steel zip-ties from Hydrotech are required to connect Checker Block units together.
- Refer to Hydrotech’s Guide Details for additional information on technical requirements.

TECHNICAL DATA

SIZE:	24" x 24" (4.0 S.F. per grid unit)
OVERALL DEPTH:	4.0"
MEDIA DEPTH:	4.0"
SURFACE AREA RATIO:	25% concrete - 75% open for greenspace
WEIGHT:	25 lbs/S.F. + media
COMPRESSIVE STRENGTH:	6,780 lbs/square inch, average (ASTM C1319)
WATER ABSORPTION:	8.8 lbs/cubic inch gallons/S.F. used
VOID SPACE:	50%

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Lindenhurst, NY Cincinnati, OH Corona, CA
Extraction/Harvesting Location		Lindenhurst, NY Cincinnati, OH Corona, CA

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.