



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

### SECTION 1. IDENTIFICATION

Product name : Hydrotech® Monolithic Membrane 6125®

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity : Category 2

#### Other hazards

This product when heated at high temperatures during application, can release vapors and/or hydrogen sulfide. Dark Black-Brown, characteristic asphaltic odour or "rotten egg" odour if H<sub>2</sub>S present, but odour is unreliable warning, since it may deaden the sense of smell. Prolonged or repeated skin contact can cause drying of the skin which may produce irritation or dermatitis. At higher concentrations of H<sub>2</sub>S (above 10 ppm), hydrogen sulphide is extremely toxic by inhalation.

#### GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H351 Suspected of causing cancer.

Supplemental Hazard State- : Hydrogen sulphide is extremely toxic by inhalation.



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

ments

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

**Storage:**  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

#### Components

| Chemical name                                    | CAS No./Unique ID | Classification | Concentration (% w/w) |
|--------------------------------------------------|-------------------|----------------|-----------------------|
| Asphalt                                          | 8052-42-4         | Carc. 2; H351  | $\geq 30 - \leq 60$   |
| glass, oxide, chemicals                          | 65997-17-3        |                | $\geq 10 - \leq 30$   |
| Lubricating oils (petroleum), hydrotreated spent | 64742-58-1        |                | $\geq 7 - \leq 13$    |
| Rubber natural                                   | 9006-04-6         |                | $\geq 1 - \leq 5$     |
| silicon dioxide                                  | 7631-86-9         |                | $\geq 0.5 - \leq 1.5$ |
| Carbon black, amorphous                          | 1333-86-4         |                | $\geq 0.1 - \leq 1$   |

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
At elevated temperatures, product mist or vapours may irritate the mucous membranes of the nose, the throat, bronchi, and lungs. Dizziness, headaches, nausea, unconsciousness. May release poisonous hydrogen sulphide gas.



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

|                                                             |                                                                                                                                                                                                                        |
|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| In case of skin contact                                     | : Take off contaminated clothing and shoes immediately.<br>Wash off with soap and plenty of water.<br>If symptoms persist, call a physician.                                                                           |
| In case of eye contact                                      | : Remove contact lenses.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.                                                                                                     |
| If swallowed                                                | : Clean mouth with water and drink afterwards plenty of water.<br>Do not induce vomiting without medical advice.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, both acute and delayed | : No known significant effects or hazards.<br>No information available.<br>Suspected of causing cancer.                                                                                                                |
| Notes to physician                                          | : Treat symptomatically.                                                                                                                                                                                               |

---

### SECTION 5. FIRE-FIGHTING MEASURES

|                                                |                                                                                                                                                                                                                                                                           |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                   | : Foam<br>Dry powder<br>Carbon dioxide (CO <sub>2</sub> )<br>Water spray<br>Sand                                                                                                                                                                                          |
| Unsuitable extinguishing media                 | : Water jet                                                                                                                                                                                                                                                               |
| Hazardous combustion products                  | : No hazardous combustion products are known                                                                                                                                                                                                                              |
| Further information                            | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>May release poisonous hydrogen sulphide gas. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.                                                                                                                                                                                                          |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

|                                                                     |                                                                                                                                                                                                                      |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Deny access to unprotected persons.                                                                                                                                          |
| Environmental precautions                                           | : Do not flush into surface water or sanitary sewer system.<br>If the product contaminates rivers and lakes or drains inform respective authorities.<br>Local authorities should be advised if significant spillages |



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

cannot be contained.

Methods and materials for : Pick up and arrange disposal without creating dust.  
containment and cleaning up : Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against : Normal measures for preventive fire protection.  
fire and explosion

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.  
Provide good ventilation in process area to prevent formation of vapour. Avoid breathing vapours. The inherent toxic and olfactory (sense of smell) fatiguing properties of hydrogen sulphide require that air monitoring alarms be used if concentrations are expected to reach harmful levels such as in enclosed spaces, heated transport vessels and spill or leak situations. Respiratory protection gear must be in use at all times. Wear protective clothing to prevent burns. Eliminate all sources of ignition, avoid sparks, flames and do not smoke in risk area. Please refer to product data sheet before use. Do not handle until all safety precautions have been read and understood.

Conditions for safe storage : Store in original container.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components              | CAS-No.    | Value type<br>(Form of exposure)   | Control parameters / Permissible concentration     | Basis |
|-------------------------|------------|------------------------------------|----------------------------------------------------|-------|
| Asphalt                 | 8052-42-4  | TWA (Fume, inhalable fraction)     | 0.5 mg/m <sup>3</sup><br>(benzene soluble aerosol) | ACGIH |
| glass, oxide, chemicals | 65997-17-3 | TWA (fibers)                       | 1 fibres per cubic centimeter                      | ACGIH |
|                         |            | TWA (Inhalable particulate matter) | 5 mg/m <sup>3</sup>                                | ACGIH |
|                         |            | TWA (fibers)                       | 1 fibres per cubic                                 | ACGIH |



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

|                                                  |            |                                    |                                                          |           |
|--------------------------------------------------|------------|------------------------------------|----------------------------------------------------------|-----------|
|                                                  |            |                                    | centimeter                                               |           |
| Lubricating oils (petroleum), hydrotreated spent | 64742-58-1 | TWA (Inhalable particulate matter) | 5 mg/m <sup>3</sup>                                      | ACGIH     |
| Rubber natural                                   | 9006-04-6  | TWA (Inhalable particulate matter) | 0.0001 mg/m <sup>3</sup> (inhalable allergenic proteins) | ACGIH     |
| silicon dioxide                                  | 7631-86-9  | TWA (Dust)                         | 80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)        | OSHA Z-3  |
|                                                  |            | PEL (respirable)                   | 0.05 mg/m <sup>3</sup>                                   | OSHA CARC |
| Carbon black, amorphous                          | 1333-86-4  | TWA (Inhalable particulate matter) | 3 mg/m <sup>3</sup>                                      | ACGIH     |
|                                                  |            | TWA                                | 3.5 mg/m <sup>3</sup>                                    | OSHA Z-1  |
|                                                  |            | TWA                                | 3.5 mg/m <sup>3</sup>                                    | OSHA P0   |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protective equipment

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

For heated product: organic vapour filter cartridge or canister with a dust, fume or mist filter (R, or P series) may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

|                          |                                                                                                                                                                                        |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          | be used when a risk assessment indicates this is necessary.                                                                                                                            |
| Skin and body protection | : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.                                             |
| Hygiene measures         | : Wash hands before breaks and immediately after handling the product.<br>Remove contaminated clothing and protective equipment before entering eating areas.<br>Avoid breathing dust. |

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                                  |                     |
|--------------------------------------------------|---------------------|
| Physical state                                   | : solid             |
| Color                                            | : black             |
| Odor                                             | : characteristic    |
| Odor Threshold                                   | : No data available |
| pH                                               | : No data available |
| Melting point/ range / Freezing point            | : No data available |
| Boiling point/boiling range                      | : No data available |
| Flash point                                      | : 601 °F / 316 °C   |
| Evaporation rate                                 | : No data available |
| Flammability (solid, gas)                        | : No data available |
| Upper explosion limit / Upper flammability limit | : No data available |
| Lower explosion limit / Lower flammability limit | : No data available |
| Vapor pressure                                   | : No data available |
| Relative vapor density                           | : No data available |
| Density                                          | : 1.15 kg/l         |
| Solubility(ies)                                  |                     |
| Water solubility                                 | : insoluble         |
| Solubility in other solvents                     | : No data available |



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

|                                          |   |                   |
|------------------------------------------|---|-------------------|
| Partition coefficient: n-octanol/water   | : | No data available |
| Autoignition temperature                 | : | No data available |
| Decomposition temperature                | : | No data available |
| Viscosity                                |   |                   |
| Dynamic                                  | : | No data available |
| Kinematic                                | : | No data available |
| Explosive properties                     | : | No data available |
| Oxidizing properties                     | : | No data available |
| Particle size                            | : | No data available |
| Particle Size Distribution               | : | No data available |
| Volatile organic compounds (VOC) content | : | 0 g/l             |

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |                                                             |
|------------------------------------|---|-------------------------------------------------------------|
| Reactivity                         | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability                 | : | The product is chemically stable.                           |
| Possibility of hazardous reactions | : | Stable under recommended storage conditions.                |
| Conditions to avoid                | : | No data available                                           |
| Incompatible materials             | : | No data available                                           |
| Hazardous decomposition products   | : | No hazardous decomposition products are known.              |

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **silicon dioxide:**

|                       |   |                                                                |
|-----------------------|---|----------------------------------------------------------------|
| Acute oral toxicity   | : | LD50 Oral (Rat): > 5,000 mg/kg<br>Method: Expert judgment      |
| Acute dermal toxicity | : | LD50 Dermal (Rabbit): > 5,000 mg/kg<br>Method: Expert judgment |

##### **Carbon black, amorphous:**

|                     |   |                                |
|---------------------|---|--------------------------------|
| Acute oral toxicity | : | LD50 Oral (Rat): > 8,000 mg/kg |
|---------------------|---|--------------------------------|



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

### **Skin corrosion/irritation**

Not classified due to lack of data.

### **Serious eye damage/eye irritation**

Not classified due to lack of data.

### **Product:**

Remarks : During application - May cause mild irritation to eyes. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Hot liquid product may cause serious thermal burns on direct contact. Hydrogen sulphide may cause eye irritation at 1 - 20 ppm and acute conjunctivitis at higher concentrations. Above 50 ppm H<sub>2</sub>S, eye irritation may include symptoms of redness, severe swelling, tearing, sensitivity to light and the appearance of 'Halos' around lights.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified due to lack of data.

#### **Respiratory sensitization**

Not classified due to lack of data.

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Suspected of causing cancer.

|             |                                                                                                              |           |
|-------------|--------------------------------------------------------------------------------------------------------------|-----------|
| <b>IARC</b> | Group 2B: Possibly carcinogenic to humans                                                                    |           |
|             | Asphalt<br>(Bitumens, occupational exposure to straight-run bitumens and their emissions during road paving) | 8052-42-4 |
|             | Group 2B: Possibly carcinogenic to humans                                                                    |           |
|             | Carbon black                                                                                                 | 1333-86-4 |
| <b>OSHA</b> | OSHA specifically regulated carcinogen                                                                       |           |
|             | silicon dioxide<br>(crystalline silica)                                                                      | 7631-86-9 |

**NTP** Not applicable

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT-single exposure**

Not classified due to lack of data.

### **Product:**

Remarks : During application: At higher concentrations of H<sub>2</sub>S (above 10 ppm), hydrogen sulphide is extremely toxic by inhalation and may cause respiratory-tract irritation, nose and throat irritation, depression of the central nervous system, respiratory failure, unconsciousness and/or death. Pulmonary edema can occur up to 24 hours after hydrogen sulphide exposure. While hydrogen sulphide emits a strong odour of rotten eggs, detection



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

by smell is not sufficient as a warning property for exposure to this substance, as it may deaden the sense of smell quickly.

### STOT-repeated exposure

Not classified due to lack of data.

#### Product:

Remarks : During application: Prolonged or repeated contact may dry skin and cause irritation. This product contains small quantities of Polycyclic aromatic hydrocarbons. Prolonged contact with these compounds has been associated with the induction of skin and lung tumours, anemia, disorders of the liver, bone marrow and lymphoid tissues. Long term inhalation of Benzene or Xylene vapours can result in bone marrow abnormalities with damage to blood forming tissues and may cause anemia and other blood cell abnormalities. Immunodepressive effects have also been reported. Hydrogen sulphide may reduce lung function; cause neurological effects such as headaches, nausea, depression and personality changes; eye and mucous membrane irritation; damage to cardiovascular system. Effect(s) from long-term exposure are similar to effects described for short-term exposure.

### Aspiration toxicity

Not classified due to lack of data.

#### Further information

#### Product:

Remarks : Carbon black (1333-86-4)  
Animal Toxicity:  
Rat, oral, duration 2 year  
Effect: no tumors  
  
Mouse, oral, duration 2 years  
Effect: no tumors  
Mouse, dermal, duration 18 months  
Effect: no skin tumors  
Rat, inhalation, duration 2 years  
Target organ: lungs  
Effect: inflammation, fibrosis, tumors  
Note: Tumors in the rat lung are considered to be related to the "particle overload phenomenon" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific. Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions. Mortality studies (human data): A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plant studied;



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

however, the increase was not related to the dose of carbon black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorohan, 2001 (UK study) found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black production workers (DEll, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was inadequate (IARC, 2010). Since the IARC evaluation of carbon black, Sorahan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorahan and Harrington. Overall, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

**IARC CANCER CLASSIFICATION:** In 2006 IARC re-affirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is "sufficient evidence" in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is "possibly carcinogenic to humans" (Group 2B)". This conclusion was based on IARC's guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found following subcutaneous injection. IARC concluded that there was "sufficient evidence" that carbon black extracts can cause cancer in animals (Group 2B).

**ICGIH CANCER CLASSIFICATION:** Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

**ASSESSMENT:** Applying the guidelines of self-classification under the Globally Harmonized System of Classification and Labeling of Chemicals, carbon black is not classified as a carcinogen. Lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rats tumors are a



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

result of a secondary non-genotoxic mechanism that has questionable relevance for classification in humans. In support of this opinion, the CLP Guidance for Specific Target Organ Toxicity - Repeated Exposure (STOT-RE), cites lung overload under mechanisms not relevant to humans. Human health studies show that exposure to carbon black does not increase the risk to carcinogenicity.

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **Carbon black, amorphous:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l  
Exposure time: 96 h

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

No data available

#### **Mobility in soil**

No data available

#### **Other adverse effects**

##### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### **International Regulations**

##### **IATA-DGR**

Not regulated as a dangerous good

##### **IMDG-Code**

Not regulated as a dangerous good

##### **Domestic regulation**

##### **49 CFR**

Not regulated as a dangerous good

##### **Special precautions for user**

Not applicable



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

---

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Carcinogenicity

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**California Prop. 65**



**WARNING:** This product can expose you to chemicals including Asphalt, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---

### SECTION 16. OTHER INFORMATION

**Full text of other abbreviations**

|                 |                                                                                    |
|-----------------|------------------------------------------------------------------------------------|
| ACGIH           | : USA. ACGIH Threshold Limit Values (TLV)                                          |
| OSHA CARC       | : OSHA Specifically Regulated Chemicals/Carcinogens                                |
| OSHA P0         | : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)               |
| OSHA Z-1        | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3        | : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts               |
| ACGIH / TWA     | : 8-hour, time-weighted average                                                    |
| OSHA CARC / PEL | : Permissible exposure limit (PEL)                                                 |
| OSHA P0 / TWA   | : 8-hour time weighted average                                                     |
| OSHA Z-1 / TWA  | : 8-hour time weighted average                                                     |
| OSHA Z-3 / TWA  | : 8-hour time weighted average                                                     |



## Hydrotech® Monolithic Membrane 6125®

Revision Date 05/07/2026

Print Date 05/07/2026

### **Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 05/07/2026

100000057336

US / Z8